



” The exclusive  
POS System

- Robust checkout PC with resistive touch monitor and stand
- Sleek appearance with bezel-free surface and aluminium housing
- Hospitality professional with IP64 protected front panel
- Fast, powerful processor with up to 2.5 GHz

Specifications - P2000/2300

		P2000	P2300
<b>System</b>	CPU	Intel Atom D525 1,80 GHz (fanless)	Intel Celeron G540 2.5 GHz
	System memory	2 GB DDR3 RAM	4 GB DDR3 RAM
	Chipset	Intel ICH8	Intel H61
	Compact Flash	CompactFlash card support	CFast-Card support
	Hard disk drive	160 GB HDD or 40/ 60/ 120 GB SSD, 2,5" SATA	
	Audio	On-board	
	Housing	Aluminium	
	Supported operating systems	Windows XP Embedded, Windows Embedded, Windows Embedded PosReady, Windows 7	
<b>Display</b>	Graphics chip	Intel integrated	
	LCD screen size	38.1cm (15")	
	Maximum resolution	1.024 x 768 pixels	
	Brightness	250 cd/m <sup>2</sup>	
	Touch screen	5-wire resistive	
<b>Interfaces</b>	USB 2.0	4x	
	Serial/COM	3x DB9, 1x RJ45	2x DB9, 1x RJ45
	Parallel	Available on demand	
	LAN	1 x RJ45 10/100/1000 Base-T	
	VGA	1x	
	PS/2	1x	
	Cash drawer port	1x (RJ11)	
	Audio	Line-out, mic-in, speaker	
<b>PSU</b>	Power adapter	90 watts	180 watts
<b>Other</b>	Dimensions (WxHxD)	323,6 x 264,2 x 368 mm	
	Weight	7.6 kg	
	Operating temperature	0 to 40 °C	
	Certification	CE, FCC, RoHS, IP64-Front	
	Mount	VESA 100 mm	
<b>Options</b>	Magnetic stripe reader	Choice of MSR (tracks 1, 2, 3), MSR + iButton reader, MSR + smart card reader + iButton reader, MSR + smart card reader + fingerprint reader	
	Customer display	VFD, 2 x 20 characters	
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") screen size	
	Barcode scanner	1D or 2D barcode scanner (optional RFID capability)	
	Waiter lock	iButton (optional RFID capability)	
	RFID	13.56 MHz (MIFARE)	
	Colours	black, white	
	UPS	up to 1 hour battery back-up	

Your Dealer